_							_	
	FOR OFFICIAL USE							
and the second second								
		4						
	Nation	al						
	Qualifi	catio	ns			Mai	<sup>-</sup> k	
	2017							
X723/76/01					Engine	ering S	Science	
THURSDAY 25 MAY								
1:00 PM – 3:00 PM								
					*	× 7 2 3	7601*	
Fill in these boxes and rea	d what is n	rinted b	pelow					
Full nome of centre								
Full name of centre				Town				
Forename(s)		Surnar	ne			Numbe	r of seat	
Date of birth								
Day Month	Year		Scottish car	ndidate	e number			
Total marks — 90								
SECTION 1 — 20 marks								
Attempt ALL questions.								
Attempt ALL questions.								
Show all working and units where appropriate.								
The number of significant figures expressed in a final answer should be equivalent to the least significant data value given in the question. Answers that have two more figures or one loss								
figure than this will be accepted.								
Reference may be made to	Reference may be made to the Engineering Science Higher Data Booklet.							
Write your answers clearly in the spaces provided in this booklet. Additional space for answers is provided at the end of this booklet. If you use this space you must clearly identify the question								
number you are attemptin	g.	÷	·	-		-	·	
use <b>diue</b> or <b>diack</b> ink.								

Before leaving the examination room you must give this booklet to the Invigilator; if you do not, you may lose all the marks for this paper.





ſ



MARKS DO NOT WRITE IN THIS MARGIN 2. A concurrent force system is shown below. 1100 N ′51° θ 65°, R 510 N Calculate the magnitude of the force R, and the angle  $\boldsymbol{\theta},$  to maintain equilibrium. 4



**3.** A beam to be used in the construction of a new holiday cottage is being tested.



3

Calculate, by taking moments about B, the vertical reaction at A.



A water feature in a children's play area is designed to pump jets of water when a child blocks the light to a darkness sensor.



A circuit diagram of the system is shown below.



(a) Calculate the current flowing through the LDR. ( $V_{be} = 0.7 V$ )

[Turn over

1



(cor	tinued)	MARKS	DO NOT WRITE IN THIS MARGIN
(b)	Calculate the current flowing through the variable resistor.	<b>1</b>	
(c)	Calculate the base current flowing into the transistor.	<b>1</b>	
Driv an i	erless vehicles are an example of an emerging technology that may have mpact on our day-to-day lives.	2	
(a)	Describe two economic impacts of driverless vehicles.	2	
	1	-	
	2	-	
		-	

4.

5.





SECTION 2 — 70 marks Attempt ALL questions

- 7. A control room in a chemical plant monitors many different systems.

(a) Part of a logic diagram for a control system is shown below.



(i) Complete the Boolean equation for this logic diagram.

<u>Z</u> =



MARKS DO NOT WRITE IN THIS MARGIN

\* X 7 2 3 7 6 0 1 0 8 \*

## 7. (a) (continued)

#### Α В С D Ε Ζ

(ii) Complete the truth table for this logic diagram.

(iii) Draw the NAND equivalent for the logic diagram, shown opposite.

[Turn over



Page 09

MARKS DO NOT WRITE IN THIS MARGIN

7.	(cor	ntinue	d)		MARGI
	(b)	An el autor	ectronic engineer is asked to design the control system for an <b>matic</b> sprinkler for the chemical plant.		
		Desci would	ribe one skill and one piece of knowledge the electronic engineer d use to complete this task.	2	
		Skill _			
		Know	/ledge		
	(c) An extension to the chemical plant building is proposed.				
		(i)	Describe a role that an environmental engineer would take in the design of the extension.	2	
		(ii)	Describe a positive and a negative economic impact for the <b>plant</b> by it becoming more environmentally friendly.	2	
			Positive impact		
			Negative impact		

3

8. A prototype of a delivery drone is being tested.



A proportional control system changes the speed of the rotor blades to reach the user's desired height for the drone. An altimeter is used to monitor the current height of the drone.

(a) Complete the control diagram for the drone.



[Turn over



(b) Part of an electronic engineer's design for the control system for one of the drone's motors is shown below.



During testing it was found that the motor requires a current of  $97 \,\text{mA}$  for the drone to hover. The transistor has a current gain of 210.

Calculate the value of  $\rm V_1$  required to make the drone hover.

3

MARKS DO NOT WRITE IN THIS MARGIN



#### MARKS DO NOT WRITE IN THIS MARGIN

## 8. (continued)

(c) The diagram below shows another part of the control system. It combines a signal for any required changes to the motor speed ( $V_A$ ) with the signal required to keep the drone hovering ( $V_{HOVER}$ ).



Calculate, using your answer for  $V_1$  the value of  $V_{\text{HOVER}}.$  (Assume that  $V_A$  is 0 V at this point).

2



[Turn over

(d) The value of  $V_A$  is set using the circuit below. It compares the drone's current height with the operator's desired height.



During testing  $V_{\rm H}$  was changed to 3.0 V and  $V_{\rm A}$  was found to be 1.6 V. Calculate the value of  $V_{\rm ALT}$  for this condition.

2

MARKS DO NOT WRITE IN THIS MARGIN

![](_page_13_Picture_5.jpeg)

8.

(e) The complete circuit diagram is shown below.  $\rm V_{HOVER}$  is the voltage required to make the drone hover.

![](_page_14_Figure_2.jpeg)

Describe, with reference to the circuit diagram above, what happens when the operator increases the desired height.

![](_page_14_Picture_5.jpeg)

MARKS DO NOT WRITE IN THIS MARGIN

(f) The diagram below shows a further sub-system which will light a series of LEDs when light levels are low

DO NOT WRITE IN THIS MARGIN

![](_page_15_Figure_2.jpeg)

The characteristics of the LDR are shown in the graph below.

![](_page_15_Figure_4.jpeg)

## 8. (f) (continued)

The LEDs must switch on when the light level drops to 200 lux. The MOSFET switches on when Vgs = 3.6 V

Calculate, with reference to the graph opposite, the required value of R.

2

MARKS DO NOT WRITE IN THIS MARGIN

[Turn over

![](_page_16_Picture_5.jpeg)

9. A team of engineers are working together to design a new theme park ride.

![](_page_17_Figure_1.jpeg)

(a) Each of the ride cars is supported by mild steel beams as shown. When the ride is operating the force on a beam was found to be 900.0 N.

![](_page_17_Figure_3.jpeg)

(i) Calculate the working stress of the beam.

![](_page_17_Picture_5.jpeg)

Page 18

MARKS DO NOT WRITE IN THIS MARGIN

## 9. (a) (continued)

(ii) Calculate the strain of the beam.

(iii) Calculate the factor of safety of the beam.

(iv) Comment on the appropriateness of the factor of safety of the beam.

[Turn over

MARKS DO NOT WRITE IN THIS MARGIN

2

2

![](_page_18_Picture_5.jpeg)

(b) The ride has eight cars. Each car is subjected to wind resistance of 130 N as shown in the diagram below.

![](_page_19_Figure_2.jpeg)

(i) Calculate the torque produced by the drive shaft to overcome the total wind resistance.

2

MARKS DO NOT WRITE IN THIS MARGIN

![](_page_19_Picture_5.jpeg)

![](_page_20_Figure_0.jpeg)

![](_page_20_Picture_1.jpeg)

(c) A microcontroller is used to control the speed of the motor.

Sketch a graph to show how pulse width modulation could be used to gradually increase the speed of a motor from rest. Your graph should include at least 6 pulses.

MARKS DO NOT WRITE IN THIS MARGIN

2

![](_page_21_Picture_3.jpeg)

(d) As the ride spins, a force of 1030 N acts on a point of the structure as shown in the diagram below.

![](_page_22_Picture_2.jpeg)

Calculate, using simultaneous equations, the magnitude of the forces in members M1 and M2.

5

![](_page_22_Picture_5.jpeg)

MARKS DO NOT WRITE IN THIS MARGIN

![](_page_23_Figure_0.jpeg)

**10.** A car manufacturer uses a pneumatic system during the production of car doors.

DO NOT WRITE IN THIS MARGIN

![](_page_23_Picture_2.jpeg)

	(cor	ntinue	ed)	
	(a)	(i)	Describe, using appropriate terminology, the operation of the pneumatic circuit.	6
			When the system is at rest and valve 2 is actuated	
		After	installation the system is altered to meet the following criteria:	
		1.	the system should be started using an electronic signal;	
		2.	the instroking sequence should be delayed.	
		(ii)	State the components and explain where they should be placed in the circuit for the changes to take place.	6
			1. Component(s)	
			Explanation	
			2. Component(s)	
			Explanation	
			[ Turn over	

After the doors have been assembled, an automated system is used to ensure quality checks are made.

THIS

Part of the system operates on the following sequence:

- A motor must switch on to move doors along a conveyor;
- A light sensor detects when the door has reached the inspection point;
- A pneumatic piston outstrokes for 1 second and diverts every fourth door for inspection;
- If an operator presses the sampling switch when a door is in position it will also be diverted using the piston;
- When a door is diverted a checking light flashes on and off 6 times over 3 seconds;
- This system continually repeats.

The relevant microcontroller connections are shown in the table below.

Inputs	Pins	Outputs
	7	Pneumatic Piston
	6	Conveyor Motor
	5	Checking Light
	4	
	3	
	2	
Sampling Switch	1	
Light Sensor	0	

Light Sensor (High signal indicates a door.)

![](_page_25_Picture_12.jpeg)

![](_page_26_Figure_0.jpeg)

## [END OF QUESTION PAPER]

![](_page_26_Picture_2.jpeg)

#### MARKS DO NOT WRITE IN THIS MARGIN

## ADDITIONAL SPACE FOR ANSWERS

![](_page_27_Picture_2.jpeg)

#### MARKS DO NOT WRITE IN THIS MARGIN

## ADDITIONAL SPACE FOR ANSWERS

![](_page_28_Picture_2.jpeg)

[BLANK PAGE]

Г

L

DO NOT WRITE ON THIS PAGE

![](_page_29_Picture_2.jpeg)

[BLANK PAGE]

L

DO NOT WRITE ON THIS PAGE

![](_page_30_Picture_2.jpeg)

## [BLANK PAGE]

## DO NOT WRITE ON THIS PAGE

#### Acknowledgement of Copyright

Section 1 Question 4CaseyMartin/Shutterstock.comSection 1 Question 5Chesky/shutterstock.comSection 1 Question 6Stephen VanHorn/shutterstock.comSection 2 Question 7Ton Snoei/shutterstock.comSection 2 Question 8gualtiero boffi/shutterstock.com

![](_page_31_Picture_4.jpeg)